



F1- ME9-CL (16,600 Kg)

- ENGINE	Monocylinder 2 strokes
- CRANKCASE	Magnesium
- CYLINDER	Aluminium, 6 ports with nickel-silicon plating
- PISTON	2 rings, thickness 1.2mm chromed steel
- COOLING:	Natural air
- DIAMETER & STROKE	66x56.8
- DISPLACEMENT	194.22cc
- COMPRESSION RATIO	11:1
- INLET	Crankcase reed valve with 4 petals
- CARBURETOR	Walbro WB37C
- MAX POWER	29hp at 8000 Rpm
- STARTING	Dual Start (Manual + Electric starter)
- TRANSMISSION	POLY-V Belt
- REDUCTION	Pulley ratio 1/2.88
- ENGINE SUPPORTS	4 engine rubber mounts-silent block
- FUEL	Unleaded gasoline + 2.5% of <i>synthetic oil</i>
- ROTATION SENSE	Frontal anti-clockwise
- AIR FILTER	Airbox
-Battery charge	Output power 80W at 5000 Rpm
- SPARK PLUG CAP	Antijamming
- EXHAUST	With aluminum silencer
- THRUST	78 Kg with 2 blade prop - Helix Ø 125 78 Kg with 2 blade prop - Helix Ø 130

LEGENDA / LEGEND

V = Verticali - Verticals
R = Rovesciati - Reverseds
A = A 45° - At 45°
9 = A 90° - At 90°
2C=doppia candela - double spark plugs
M = Manuale - Manual
E = Avviamento Elettrico - Electric starter
C = Con caricabatteria - With battery charge
CL= corsa lunga- long stroke

MINARI ENGINE by Parmakit S.r.l.

Strada Antolini, 18/C - 43044 Lemignano di Collecchio - Parma (ITALY)
Tel: 0039-(0)521-30.34.13 - Fax: 0039-(0)521-54.33.79
E-Mail: info@minari-engine.com
WEB: www.minari-engine.com / www.parmakit.com